IMAX B6 80W Multi-function 1-6 Cells XT60 LiPo Battery Digital Balance Charger Discharger with Cables Line Input 12V 16V 1Set

Features:

Optimized operating software
Internal independent lithium battery balancer
Balancing individual cells battery discharging
Adaptable to various type of lithium battery
Automatic charging current limit
Processing time limit

Specifications:

Operating voltage range: DC 12-16V
Circuit power: Max. Charge power 80W / Max. Discharge power 10W
Charge Current Range: 0.1 ~ 6.0A
Discharge Current Range: 0.1 ~ 2.0A
LiLon / LiPo / LiFe: 1 ~ 6 cells
NiMH / NiCD: 1 ~ 15 cells
Size: 133 * 86 * 33mm

Package included:

1 * Battery Balance Charger
3 * Cables

发射机与接收机配对情况

"√"表示可配对成功

接收机 / 发射机	2A代系统 iA10	2A代系统 iA10B	1代系统 R9B	1代系统 R6B	2A代系统 iA6	2A代系统 iA6B	2A代系统 A6	2代系统 iR4	2A代系统 iA4B	2A代系统 A3	1代系统 GR3E	1代系统 GR3F
FS-i10	√	√	√	√	√	√	√	√	√	√	√	√
FS-TH9X			√	√							√	√
FS-i6	√	√	√	√	√	√	√		√	√	√	√
FS-i6S	√	√			√	√	√		√	√		
FS-T6			√	√							√	√
FS-CT6B			√	√							√	√
FS-i4	√	√	√	√	√	√	√		√	√	√	√
FS-T4B			√	√							√	√
FS-GT3C			√	√							√	√
FS-GT3B			√	√							√	√
FS-GT2F	√	√	√	√	√	√	√		√	√	√	√
FS-GT2E	√	√	√	√	√	√	√		√	√	√	√
FS-GT2G	√	√	√	√	√	√	√		√	√	√	√
FS-GT2B			√	√							√	√
FS-GT2			√	√							√	√
FS-iT4			√	√				√			√	√
FS-iT4S	√	√	√	√	√	√	√	√	√	√	√	√