

## IMAX B6 80W Multi-function 1-6 Cells XT60 LiPo Battery Digital Balance Charger

Discharger with

Cables Line Input 12V 16V 1Set

Cables Line Input 12V 16V 1Set Features:

Optimized operating software

Internal independent lithium battery balancer Balancing individual cells battery discharging Adaptable to various type of lithium battery Automatic charging current limit

Processing time limit

**Specifications:** 

Operating voltage range: DC 12-16V Circuit power: Max. Charge power 80W /

Max. Discharge power 10W

Charge Current Range: 0.1 ~ 6.0A Discharge Current Range: 0.1 ~ 2.0A

LiLon / LiPo / LiFe: 1 ~ 6 cells NiMH / NiCD: 1 ~ 15 cells Size: 133 \* 86 \* 33mm

Package included:

1 \* Battery Balance Charger

3 \* Cables

发射机与接收机配对情况												
接收机发射机	2A代系统 iA10	2A代系统 iA10B	1代系统 R9B	1代系统 R6B	2A代系统 iA6	2A代系统 iA6B	2A代系统 A6	2代系统 iR4	2A代系统 iA4B	2A代系统 A3	1代系统 GR3E	1代系统 GR3F
FS-i10	1	1	1	1	1	1	1	1	1	1	<b>√</b>	1
FS-TH9X		*	1	1							1	1
FS-i6	~	<b>√</b>	1	1	1	1	~		1	1	1	~
FS-i6S	4	1			1	1	~		1	1		
FS-T6			1	4							<b>√</b>	<b>V</b>
FS-CT6B			1	1	38						1	1
FS-i4	~	1	1	1	1	1	1		1	1	1	1
FS-T4B			√	1							<b>√</b>	1
FS-GT3C			1	1							1	1
FS-GT3B			1	1							<b>√</b>	1
FS-GT2F	<b>~</b>	√	<b>√</b>	1	1	1	<b>1</b>		<b>1</b>	1	1	1
FS-GT2E	<b>√</b>	√	1	1	1	1	1		1	<b>√</b>	1	1
FS-GT2G	<b>√</b>	1	√	1	1	1	1		1	1	1	<b>√</b>
FS-GT2B	35		1	1							<b>V</b>	~
FS-GT2			1	1							<b>V</b>	1
FS-iT4		· V	1	1				<b>√</b>			<b>√</b>	1
FS-iT4S	<b>4</b>	1	1	1	1	1	<b>V</b>	1	1	1	1	1

# 2S-6S Lipo Battery Charging Parallel Board Charger Plate T Plug for Imax B6 B6AC B8 6 in 1

#### characteristics:

High Quality 2S-6S Lipo Parallel Charging Board Charger Plate T Plug for Imax B6 B6AC B8 6in1 Our parallel charge cards allow you to charge and balance up to six batteries simultaneously without a clutter of wires. Built from the highest quality materials, they give you the best possible connection every time you charge your batteries. The board is already wired in parallel, all you need to do is plug in your batteries charge and balance connectors to the board make sure all the batteries are the same cell count. Each board can charge up to six batteries, from 2S up to 6S, up to a 30A charging rate.

### **Description:**

- 1.100% brand new
- 2 .: parallel board For lipo balance load charger, such as Imax B6 B8 B6AC, UNA6, and other balance chargers
- 3. Save your money, Save your time, 6 AKKUS at One Time (2s-6s: 2s \* 6s or 3s \* 6s or 4s \* 6s, 5s or 6s or 6s \* 6s), just take 1 / 6 of the customary time
- 4. You can serial connection 3pcs this board charge in parallel a time, it means that you can charge max 18pcs AKKUS at the same time

#### detail:

- 1.Symmetrical output line using 20AWG multi-strand silicone thread.
- 2. Main output line using high quality 14AWG multi-strand silicone wire.
- 3. T-Plug with a safety plug silicone cap.
- 4. High-quality AMASSER output plug.
- 5. Thick copper PCB, can spend 30A charging current safely

package size: 16 \* 8 \*

4cm / 6.4 \* 3.2 \* 1.6 in package weight: 146g / 5.1oz

**Note: Battery not included**